



Automotive

Wheel balancers

ADAPTERS AND ACCESSORIES



ADAPTERS AND ACCESSORIES

Professional centring of all types of wheels

Clamping tools for PROBALANCE

Adapter with centring studs SR 4 (4 holes)

(98 - 100 - 108 - 110 - 114.3 - 120 - 130 mm)

518 89 58 (Standard clamping)

518 89 89 (Pneumatic clamping)

Adapter with centring studs SR 5 (5 holes)

(100 - 108 - 112 - 114.3 - 120 - 139.7 - 160 mm)

518 89 65 (Standard clamping)

518 89 96 (Pneumatic clamping)

Adapter with centring studs SR 5/2 (5 holes)

(98 - 110 - 118 - 120.65 - 127 - 130 - 140 mm)

518 89 72 (Standard clamping)

518 90 05 (Pneumatic clamping)

Adapter with centring studs SR USA

(101.6 - 114.3 - 130 - 139.7 - 165.1 - 170)

518 90 29 (Standard clamping)

518 90 36 (Pneumatic clamping)

The adapters with centring studs SR 4 and SR 5 include 68 mm and 86 mm bolts.
The adapters with centring studs SR USA include 50 mm and 80 mm bolts.

Ref. No.	Description/clamping range
518 62 35	Clamping hood RL for alloy rims
518 89 10	VL cone (97 - 170 mm)
518 89 27	Spacer G / 36 (for the VL cone)
518 89 03	J cone (101 - 119 mm)
518 68 57	Stepped cone (56 - 66 - 71.5 mm)
518 68 70	Stepped cone for BMW (57 - 72.5 - 74 mm)
518 61 70	Duo-expert system case (54 - 75 mm)
519 99 50	Caliper
518 61 25	Universal quick adapter UH 20/2 (95 - 210 mm / 3 - 4 - 5 holes)

The pictures shown in the brochure may differ from the delivered equipment and include optional accessories. For detailed information on optional accessories, please request the respective brochure or visit us at www.rema-tiptop.com.

Motorbike and quad centring kits

Ref. No. Description/type, including:

518 65 10	PRO BIKE II module ECO (PROBALANCE)
518 65 20	PRO BIKE II module ECO (conical shaft) <ul style="list-style-type: none">• Base plate• Centring cones (15 - 30 mm)• Motorcycle shaft (14 mm)• Pin spanner
518 65 30	PRO BIKE II module STANDARD (PROBALANCE)
518 65 40	PRO BIKE II module STANDARD (conical shaft) <ul style="list-style-type: none">• Base plate• Quick-Fix (14 mm)• Motorcycle shaft (14 mm)• Centring cones (15 - 30 mm)• Centring sleeves (15 - 28 mm)• Adapter board Standard• Pin spanner
518 65 50	PRO BIKE II module PROFI (PROBALANCE)
518 65 60	PRO BIKE II module PROFI (conical shaft) <ul style="list-style-type: none">• Motorcycle shaft (19 mm)• Centering sleeves up to 35 mm• Centring kits for mono lever wheels• Quick-Fix (19 mm)• Adapter board PROFI
518 65 70	PRO BIKE II module EXPERT (PROBALANCE)
518 65 80	PRO BIKE II module EXPERT (conical shaft) <ul style="list-style-type: none">• 9 additional motorcycle shafts (10/12/15/16/17/20/22/25/28 mm)• Distance sleeves of different diameters and lengths
518 66 50	Centring cones XL <ul style="list-style-type: none">• Shaft diameter (14 mm)• Clamping range (16 - 45 mm)
518 65 00	Quad centring kit <ul style="list-style-type: none">• Clamping range (74 - 99.5 mm)
518 66 00	PRO BIKE Quick-Fix (14 mm)
518 66 10	PRO BIKE Quick-Fix (19 mm)

Your local contact:

REMA TIP TOP GmbH Business Unit Automotive

Gruber Straße 63
85586 Poing/Germany

Tel.: +49 81 21 707-234

Fax: +49 81 21 707-222

www.rema-tiptop.com
info@tiptop.de